

- Plug-in electronic timer for variable control
- All metal construction
- No warm-up time
- Options: sealers with sliding cutter also available
- Round wire option available for seal and cut

Our FS-series impulse hand sealers seal poly bags and other thermoplastic materials quickly and efficiently without any warm-up time. Depending on the model of the machine, materials up to 20” wide and 20mil total thickness can be sealed. FS-Series impulse sealers are available in 4”, 8”, 12”, 16”, and 20” with a 2mm , 3mm or 5mm seal width. Manufacturers’ kit includes two elements, two PTFE covers and 1 blade (if cutter unit is ordered.) Cut and Seal Applications: Round wire heating elements are available for cut and seal applications. When ordering, add the letters rnd to the model number. (Example: 12” hand sealer with round cut wire – FS-300rnd.)

Easy to Operate: Set the timer; insert the bag between the sealing bars, then press down and release. We recommend that the user hold the sealing arm down for an additional second or two to ensure enough time for the bag to set and cool.

Replacement kits that include (2) Elements, (2) PTFE Covers, (2) PTFE Adhesives, and (1) blade for cutter units are available to order. To order, use part RK-model#



Model #	Seal Length	Seal Width	Power	Weight (lbs)
FS-100	4”	2MM	132W	5
FS-200	8”	2MM	245W	7
FS-205	8”	5MM	315W	9
FS-300	12”	3MM	400W	11
FS-305	12”	5MM	425W	13
FS-400	16”	3MM	440W	15
FS-405	16”	5MM	600W	17
FS-500	20”	3MM	755W	18
FS-505	20”	5MM	800W	20

FS-Series impulse sealers with cutters are available in 8” and 12” with a 2mm, 3mm, or 5mm seal width. Seal and trim tubing in one step. Cutter is located ¼” above the seal line.

Model #	Seal Length	Seal Width	Power	Weight (lbs)
FS-200C	8”	2MM	245W	9
FS-205C	8”	5MM	315W	11
FS-300C	12”	3MM	400W	12
FS-305C	12”	5MM	425W	14

