

STAINLESS STEELCONTINUOUS BAND SEALER W/ DRY INK CODING

Model: HL-M810

Seal & Print at the Same Time



SPECIFICATIONS	
POWER	110V / 60Hz
MOTOR POWER	50W
SEALING SPEED	0-630 INCHES/MINUTE
SEAL WIDTH	10MM
SEALING POWER	300 X 2
TEMPERATURE RANGE	0-300°C
PRINTING HEATING POWER	40 X 2
CONVEYOR SIZE	38" X 6"
MAX CONVEYOR LOAD	22-LBS
BAG SIZE (FILLED) VERTICAL UNIT ONLY	MINIMUM - 7-7/8" / MAXIMUM - 12"
CHARACTER SIZE	18PT (3X5X7MM) – 2 LINES 10.5PT (2X3X7MM) – 3 LINES - OPTIONAL 20 CHARACTERS/LINE
DIMENSIONS	H: 38" X 16" X 14" / V: 38" X 16" X 26"

HL-M810 Left Feed Band Sealer is suitable for sealing all types of thermoplastic materials and bags. This sealer can be used in a variety of fields such as the food, medical, and cosmetic industries. Can seal 20-30 6" poly bags in one minute. HL-M810 uses dry ink coding to print numbers or letters on the seal line.

Standard Features:

- Durable stainless steel construction
- Easy to operate minimal operator training
- Fast warm up time
- Solid state digital temperature controller to maintain seal bars at proper temperature for consistent seal quality
- Fully adjustable conveyor (conveyor height and depth in relation to seal bars can be adjusted)
- Motorized rubber conveyor for speed control
- Knurled pressure rolls with variable pressure adjustment
- Sealing method constant/direct heat accompanied with a pair each of cooling and heating blocks
- Unit feeds left to right (Option: right feed available)
- Spare parts includes: PC Board, PTFE belt, wheel belt, fuse, motor brush, heating element, silica gel ring, silicone pin, and type set

Options:

- Stainless steel stand for horizontal models
- Dry ink coding font size 10.5PT (standard is 18PT)
- Right to left feed
- Digital counter to keep track of sealed packages
- 220V Voltage



STAINLESS STEEL CONTINUOUS BAND SEALER W/ DRY INK CODING Model: HL-M810





8820 Baird Avenue • Northridge, CA 91324 • T: 818-718-8818 • F: 818-718-8857

☑ info@sealersales.com

www.sealersales.com